

Client: _____ Project: _____ Type: _____ Qty: _____

Technical Specifications

INPUT VOLTAGE

AC 120V

FREQUENCY

50~60HZ

COLOR TEMPERATURE

2700K, 3000K, 4000K, 5000K

COLOR RENDERING INDEX

90

DISTRIBUTION

Frosted Lens

IP RATING

Damp / Wet Location* Listed

BEAM ANGLE

120°

LIFE SPAN

50,000hrs

DIMMING

100%-10% Dimming

Product Showcase




Product Features

FEATURES

- DL Series Surface Mount Downlight can be used for retrofit / newconstruction applications. It can be installed directly with 2x2 / 2x4/ 4x4 junction box and most 5" or 6" housing.
- Up to 80% in energy savings compared to incandescent bulbs.
- 100%-10% dimming range, compatible with standard incandescent dimmer or ELV dimmer.
- Includes standard E26 adapter.
- Wet Location Listed for 5000K model. Damp Listed for all other models.
- ETL / cETL Listed, Energy Star
- 5 Year Warranty



Dimensions

**A**
 ø185mm
 (ø7.28")
B
 27.5mm
 (1.08")

Ordering Information

 DL - 15 CCT F - WH S

Series	Wattage	CCT	Lens	Finish	Input
DL	15 - 15W	50 - 5000K (1200lm)	F - Frosted Lens	WH - White	S - 120V
		40 - 4000K (1150lm)			
		30 - 3000K (1100lm)			
		27 - 2700K (1050lm)			