

Client: _____ Project: _____ Type: _____ Qty: _____

Technical Specifications

INPUT VOLTAGE

AC 110~277V

FREQUENCY

50~60HZ

COLOR TEMPERATURE

4000K, 5000K

COLOR RENDERING INDEX

80

BEAM ANGLE

110°

IP RATING

IP65

OPERATING TEMPERATURE

-40°C~+50°C

LIFE SPAN

50,000hrs

DIMMING

0-10V



Product Showcase



FEATURES

- Energy saving, long lasting LED High Bays perfect for warehouse, factory, workshops, gymnasiums and more.
- Easy to install and operate.
- IP65 Rated suitable for outdoor / wet applications.
- UL / cUL Listed, DLC 4.3 Premium Listed.



Product Features

Dimensions



Power	A	B
100W - 200W	193mm (7.60")	Φ298mm (11.73")

Ordering Information

HB - Wattage CCT C - HM BK UD

Series	Wattage	CCT	Lens	Mounting	Finish	Input Voltage & Dimming
HB	100 - 100W (14500lm)	50 - 5000K	C - Clear	HM - Hook	BK - Black	UD - 110-277V & 0-10V Dimming
	150 - 150W (21750lm)	40 - 4000K	PR - Prismatic Reflector			
	200 - 200W (29000lm)					

Accessories/Option Adder

Part #	Description
EMB-25W	EMB-25W External 25W Vertical Emergency Battery for UFO High Bays (Field or Factory install)
-CORD	6 Foot Cord
-PLUG	6 Foot Cord and 3 Prong Plug

HB**SERIES****LED BAY LIGHT****ALS**
Advantage Lighting Solutions

DLC Listing

Part Number	OEM Part Number	DLC Classification
HB - 100 50 C - HM BK UD	AST-HB07-100WSACGD1-a[S;Blank][M;Blank]50	Premium
HB - 100 40 C - HM BK UD	AST-HB07-100WSACGD1-a[S;Blank][M;Blank]40	Premium
HB - 150 50 C - HB BK UD	AST-HB07-150WSACGD1-a[S;Blank][M;Blank]50	Premium
HB - 150 40 C - HB BK UD	AST-HB07-150WSACGD1-a[S;Blank][M;Blank]40	Premium
HB - 200 50 C - HB BK UD	AST-HB07-200WSACGD1-a[S;Blank][M;Blank]50	Premium
HB - 200 40 C - HB BK UD	AST-HB07-200WSACGD1-a[S;Blank][M;Blank]40	Premium